

# RESTO SPACHELMASSEN

**Vertrieb farbiger Kitt für Holz & Haus**

Tel.: 0 22 35-45 32 6 · Fax: 0 22 35-46 15 42

e-mail: restokitt@aol.com

Spachtelmassen I. Sotiropoulos · Carl-Schurz-Str. 155 · 50374 Erfstadt

## Technical Data sheet

**RESTOKITT UNIVERSAL EXTRA**

**Waterbased putty paste, quick drying**

18/10/05 LRD/nz

### Product description

Ready-to-use putty paste, easy to apply, offering quick drying and excellent sandability. Suitable for levelling and smoothing indoors on wood, walls and plasterboard.

### Technical data

Colour : see colours card

Binder : vinyl dispersion

Specific gravity : 1.65 kg/litre ( ± 0.02)

Practical cover rate □ : 1 sq.mt./kg per 500 ÷ 600 µm thickness.

Storage life : 18 months in original sealed container.

**NB:** Data recorded @ 20°C.(68°F.)

### Application note

Substrate preparation : Surfaces must be clean, without mould or humidity.

Application method : - spatula

Sandability : after 1 ÷ 2 hours

Overcoatable : with water-based products or solvent-type.

Tools cleaning : with water

### NOTE:

To fill up thick cracks, apply several subsequent layers of Resto Holzkitt.

Not exceeding 7 ÷ 8 mm, and allow at least one hour between them.

Do not apply when the relative humidity exceeds 75%.

Surface and ambient temperature must be above + 5 (41°F.) and below 35°C.(95°F.)

**BEWARE OF FROST.** Store the product between + 5 and 35°C.

Information provided in this technical data sheet is based upon our best experience and technical knowledge; it does not absolve the users from carrying out tests and preventive checks in order to verify the suitability for use. For further technical information about specific systems and/or special applications, please contact our TECHNICAL SERVICE.

This note replaces all the previous ones. Please, make sure to have the latest issue. The above mentioned data are meant to facilitate our customers in the use of our products.